



# Protecto Flex<sup>®</sup> Window & Door Sealing Tape For Curved and Radius Surfaces

Forms a permanent waterproofing air/vapor seal around curved and radius doors and windows that prevents air and moisture leaks.



Protecto Flex<sup>®</sup> is a 40-mil thick peel and stick flashing tape. The flexible cross-laminated top surface will expand and conform to irregular or curved surfaces while the aggressive adhesive forms a permanent bond between the window fin and the building substrate. Protecto Flex gives you a total air and water seal without having to cut and patch in the membrane to conform to irregular or curved window and door openings.



## ADVANTAGES:

- Expands and conforms to radius or curved window fins
- Aggressive adhesive forms a permanent bond between the window fins and the building substrate
- Easy to install peel and stick application
- Self seals around nails, screws and staples
- Adheres to plywood, OSB, vinyl, aluminum, metal, foam, Dens-Glass Gold<sup>®</sup>, \* concrete and masonry surfaces
- Protecto Flex may be left exposed up to 120 days
- Backed by over 50 years of manufacturing expertise

## SUITABLE APPLICATIONS:

- Window and door perimeters to the building substrate
- Other areas where a water or air seal is needed

## INSTALLATION INSTRUCTIONS:

PLEASE NOTE: Surfaces should be clean, dry and free of dirt and other foreign materials. do not use any solvent-based sealant on or around Protecto Flex Tape. do not use in direct contact with flexible (plasticized) polyvinyl chloride (i.e. flexible "J" channel). Protecto Flex Tape is recommended for the curved and radius portion of windows and doors. BT25XL, BT20XL or Protecto Super Stick is recommended on ALL straight parts.

When applying Protecto Flex to masonry, concrete, black sheathing board and OSB products or Dens-Glass Gold<sup>®\*</sup>, the surface should be tested for adhesion. If adequate adhesion is not obtained, the surfaces must be primed with Protecto-Tak Spray Adhesive or Universal Water Based Primer.

Apply the horizontal (head of window/door) piece of Protecto Flex on the top of the window fin directly to building's exterior substrate. Roll tape surfaces to ensure proper adhesion.

\* Dens-Glass is a registered trademark of Georgia-Pacific Corporation.

### ROLL SIZES/ROLL PER CASE:

6" x 50'/2

9" x 50'/1

### PHYSICAL PROPERTIES:

Color: White/Gray

Thickness: 40 mil

Elongation: 500% min. (rubberized asphalt adhesive only)

Permeance: .01 perms max ASTM E-96

Max Exposure Time: 120 Days



**Premium Building Products  
That Protect**

**PROTECTO WRAP COMPANY**

**(800) 759-9727**

**[www.protectowrap.com](http://www.protectowrap.com)**