



Jiffy Seal[®] BUTYL Ice & Water Guard HT[™]

High Temperature Self Adhered Underlayment
with Protecto Wraptor[™] Tri-Layer Engineered Film

TECHNICAL DATA

Properties	Test Method	Test Results
Surface Color		Green
Thickness		30 mils
Tensile Strength	ASTM D412	>1600 psi
Elongation (adhesive only)	ASTM D412	500%
Puncture Resistance	ASTM E154	>250 psi
Low Temperature Flex	ASTM D1970	No cracks or delamination
Adhesion to Plywood	ASTM D903	4.5lb/in width (unprimed)
UV Exposure period		12 months
Operating Temperature		Up to 300°F (up to 149°C)
Permeance	ASTM E96	<.05

PACKAGING

36" x 66' roll (198 SF/Roll)

DESCRIPTION

Jiffy Seal[®] BUTYL Ice & Water Guard HT is a cold applied, self-adhering membrane composed of a proprietary slip resistant, tri-layer, woven polyolefin fabric coated on one side with a layer of high temperature recycled butyl adhesive.

FEATURES

- Proprietary RECYCLED butyl adhesive
- Recommended for High Altitude and or Highly Conductive Roof Coverings
- 12 month exposure rating
- Fully adhered system
- Proprietary Protecto Wraptor[™] Tri-Layer, Engineered Film Technology
- Proprietary slip resistant surface for added footing safety
- Seals around properly installed fasteners
- Waterproof, Air and Vapor Barrier
- Can be installed Horizontally or Vertically (as code allows)
- Can be installed on roof pitches down to 2"/12", for lower slopes contact your Protecto Wrap Representative
- Compatible with EPDM

USES

A complete waterproof roofing underlayment specifically formulated for use on very high temperature roof applications, highly conductive roof applications and high altitude applications, also can be used on new and *retro-fit* roofs, under most roof coverings. Designed for use at low slope areas, hip, ridge, valleys, rake edges, confined rake edges, around skylights and chimneys.

LIMITATIONS

Not recommended for use on roof slopes less than 2"/12" (without approval).
Not recommend for use over granulated surfaces or existing roof coverings.

SHELF LIFE

Jiffy Seal BUTYL Ice & Water Guard HT maintains optimum initial adhesion to substrates when used within one year from the date of manufacture.

STORAGE

Jiffy Seal BUTYL Ice & Water Guard HT should be stored in the original, unopened container at ambient temperatures between 40°F to 90°F (5°C to 32°C). Storage area should remain dry and out of direct sunlight. Do not remove materials from original containers until ready for use. Do not double stack pallets. Do not store rolls on end.

PREPARATION

Roof deck surface shall be clean, dry and free of any foreign materials. The roof deck surface shall be free of gaps, sharp edges and protrusions. Do not walk on surface when wet or covered with frost as there is an increase risk of injury. Metal surfaces may need to be solvent wiped and/or abraded to achieve optimum adhesion.

Priming

Prime DensGlassGold[®], DensDeck[®], masonry and concrete substrates. For other substrates such as wood composition and gypsum sheathing, prime as necessary if adhesion is found to be marginal. Refer to "Technical Letter Primer Recommendations" for more information regarding primer recommendations and "Technical Letter Adhesion to Substrates" for adhesion guidelines.

APPLICATION

Jiffy Seal BUTYL Ice & Water Guard HT can be installed on any exterior grade solid sheathing normally used for roof decking. Apply **Jiffy Seal Ice & Water Guard HT** only in fair weather conditions when air, roof deck and membrane temperatures are at 40°F (5°C) or higher.

Install membrane such that all laps shed water in both vertical and horizontal installations.

Valleys require a minimum 18" wide roll of **Jiffy Seal BUTYL Ice & Water Guard HT** centered down the full length of the valley.

Install membrane starting at the lowest point of roof slope and work up the slope.

Position the roll into the desired location, roll out the membrane and cut to length as needed.

Align the roll with edge of eave or overlap of preceding roll, pull membrane tight, start by removing a portion of the release liner and adhere to roof deck (reposition as needed prior to removing the remaining release liner).

Lift the opposing end of the membrane and remove or strip the release liner, pulling it to one side, keep membrane aligned and tight, adhere membrane to the roof deck while another person brooms the sheet flat.

Edge laps are 3" minimum and end laps are 6" minimum. All laps should be firmly pressed or rolled to ensure a positive seal.

* Additional methods and details can be found at www.protectowrap.com or call (800) 759-9727.

CLEAN UP

Dispose of waste in accordance to local requirements. Control worksite so that boxes and release liner do not present a hazard. Packaging materials and release liner can be recycled.

CAUTION

Jiffy Seal BUTYL Ice & Water Guard HT should not come into contact with solvent based products, polysulfide's, plasticized PVC roofing materials or high concentrations of resins (pitch).

Jiffy Seal BUTYL Ice & Water Guard HT incorporates a slip resistant surface; however, Protecto Wrap Company recommends the use of appropriate fall protection when installing roof underlayments.

Jiffy Seal BUTYL Ice & Water Guard HT is a moisture, air/vapor barrier; spaces under the area covered must be properly vented.

LIMITED WARRANTY

This product is covered by the Protecto Wrap Standard 10 Year Limited Warranty.

PROTECTO WRAP COMPANY
1955 South Cherokee Street
Denver, CO 80223
(303) 777-3001 • (800) 759-9727
FAX (303) 777-9273
www.protectowrap.com