

TECHNICAL LETTER—PRODUCT EXPOSURE

Protecto Wrap Company self-adhered membranes are manufactured for use in a variety of applications. During the construction process some products may be exposed to the elements prior to being covered. The following guideline can help determine the exposure limits for each of our products. If products are exposed longer than the stated limit, there may be some changes to the appearance of the products. This change is due to ultraviolet (UV) radiation and thermal cycling. The product might have small wrinkles, curling at the edges and appear faded. This should not affect the performance of the product; however, prior to covering, Protecto Wrap Company suggests inspecting the affected areas and repair as needed. If wrinkles or curling extend from a detail area or overlap a patch must be installed a minimum of 6" in all directions past the affected area(s). Please refer to "Technical Letter – Membrane Repair and Overlay" or "Technical Letter – Roofing Repair and Overlay" for more information.

If exposure limits are expected to exceed the guideline below, please contact Protecto Wrap Company for recommendations.

PRODUCT	EXPOSURE LIMITS							
	30 days	6 weeks	60 days	120 days	6 months	12 months	18 months	UV Stable*
Bridge Deck	x							
Jiffy Seal 140/60	x							
PW 100/60	x							
Protecto Bond								x
PW 100/40				x				
Protecto Seal 45								x
Stucco, EIFS, Buck Tapes		x						
BT25XL				x				
PSDS		x						
Protecto Deck								x
Energy Sill Sealer		x						
Triple Guard		x						
Plate Liner		x						
Dual Guard		x						
Rainproof 40						x		
Rainproof 60						x		
Jiffy Seal Ice & Water Guard HT						x		
Jiffy Seal Butyl Ice & Water Guard HT						x		
Ice & Water Guard	x							
Tile Flash								x
Protecto Roof								x

PROTECTO WRAP COMPANY

1955 South Cherokee Street Denver, CO 80223 1-800-759-9727 (303) 777-3001 Fax (303)777-9273 www.protectowrap.com

PRODUCT	EXPOSURE LIMITS							
	30 days	6 weeks	60 days	120 days	6 months	12 months	18 months	UV Stable*
EPDM								x
LWM 200								x
AFM, AFM-WM, AFM/SCU	x							
Whisper Mat CS	x							
AFM Detail Tape	x							
Defenseal	x							
Whisper Mat HW	x							
Peel and Heat Complete	x							
Protecto Liner 1350								x
Protecto Liner 1350 FR								x
Protecto Liner 1350 TG								x
6640 Roofing Underlayment		x						
6640-R Reinforced Roofing Underlayment					x			
6610 Seam Seal Tape				x				
6612MR Seam Seal/Metal Roof Tape	x							
6634 Air & Vapor Barrier/Wall Flashing				x				
6660 Waterproofing Membrane	x							
Flat Flash	x							

* UV stability/exposure time is defined by each individual product warranty.

Protecto Wrap Company provides the information here based on knowledge and data considered to be true and accurate at the time of publication, and is offered for the user's consideration, verification and investigation. Protecto Wrap Company does not warrant the results to be obtained or the appropriateness of the offering for the user's particular project. It is the sole responsibility of the user to read and understand all statements, recommendations or suggestions regarding conditions of sale. No statement, suggestion or recommendation herein is intended for any use that could infringe on any copyright or patent. These products may be covered by patents or patents pending. Copyright 2008. Protecto Wrap Company

PROTECTO WRAP COMPANY

1955 South Cherokee Street Denver, CO 80223 1-800-759-9727 (303) 777-3001 Fax (303)777-9273 www.protectowrap.com