

TECHNICAL LETTER—ROOFING UNDERLAYMENTS ON SLOPES LOWER THAN 2:12 PITCH

When Protecto Wrap® Self-Adhered Roofing Underlays are used as waterproofing on roofs less than 2:12, the following guidelines are recommended to reduce the possibility of a leak:

- 1.) Protecto Wrap **Ice & Water Guard™** should be used as the first course on the roof deck. This product is a unique, internally reinforced waterproofing roof underlayment, with adhesive on both sides. Starting from the low point of the roof, install a 18" course along the roof's edge. Overlay the second 36" wide course a min. of 2" in a shingle fashion up the roof. End laps should overlap a min. of 6". Leave the polyethylene release facer, found on top of the **Ice & Water Guard™**, in place (except at edge and end laps) until ready to apply the second layer of waterproofing.
- 2.) When applying the top layer, remove the polyethylene release liner on top of the **Ice & Water Guard™** and apply the **Rainproof** underlays following our standard installation procedures, while always allowing alternating seams to the first layer of **Ice & Water Guard™**. Seam laps of the second layer should be a min. of 2" and end laps a min. of 6". Care should be taken to insure that the top layer of material is lined-up straight with the edge of the roof, once the adhesive of the two membranes touch repositioning will be difficult.
- 3.) Apply a 3/8" troweled bead of **JS 160H Mastic™** to all seams, terminations, T-joints and details per industry standard for low slope waterproofing procedures.
- 4.) Follow standard plaza deck waterproofing details.

Protecto Wrap Company provides the information here based on knowledge and data considered to be true and accurate at the time of publication, and is offered for the user's consideration, verification and investigation. Protecto Wrap Company does not warrant the results to be obtained or the appropriateness of the offering for the user's particular project. It is the sole responsibility of the user to read and understand all statements, recommendations or suggestions regarding conditions of sale. No statement, suggestion or recommendation herein is intended for any use that could infringe on any copyright or patent. These products may be covered by patents or patents pending. Copyright 2008. Protecto Wrap Company

PROTECTO WRAP COMPANY

1955 South Cherokee Street Denver, CO 80223 1-800-759-9727 (303) 777-3001 Fax (303)777-9273 www.protectowrap.com

September 2009