



Premium Building Products  
That Protect

# Rainproof 60 High Performance Roof Underlayment™

Roofing underlayment

## TECHNICAL DATA

| Properties            | Test Method | Test Results              |
|-----------------------|-------------|---------------------------|
| Surface Color         |             | Mottled White             |
| Thickness             |             | 60 mils                   |
| Tensile Strength      | ASTM D412   | 800 psi                   |
| Elongation            | ASTM D412   | 500%                      |
| Puncture Resistance   | ASTM E154   | 150 psi                   |
| Low Temp Flex         | ASTM D1970  | Unaffected at 0°F (-18°C) |
| Nail Sealability      | ASTM D1970  | Pass                      |
| Adhesion to Plywood   | ASTM D903   | 3.0 lb/in width           |
| UV Exposure period    |             | 12 months                 |
| Operating Temperature |             | Up to 250°F (Up to 121°C) |

## PACKAGING

36" x 50' roll (150 SF/Roll)

## DESCRIPTION

**Rainproof 60 High Performance Roof Underlayment™** is a cold applied self-adhering SBS modified, rubberized asphalt sheet waterproofing underlayment. **Rainproof 60** is internally reinforced with a strong non-woven polyester fabric. The membrane has a white reflective fabric topping.

## FEATURES

- 12 month exposure rating
- Fully self adhered roofing underlayment system
- 2½" zip strip release liner for ease of edge overlap adhesion
- Durable White reflective topping for added footing safety and heat reduction
- Seals around properly installed fasteners
- Can be installed Horizontally or Vertically (as code allows)
- Can be installed on roof pitches down to 2"/12" (For lower slopes contact your Protecto Wrap Representative.)

## USES

Used as a complete waterproof roofing underlayment on new and retro-fit\* roofs under most roof coverings. Can be used at low slope areas, Hip, Ridge, Valleys, Rake edges, Confined Rake edges, around skylights and chimneys.

## LIMITATIONS

Not recommended for use under high temperature roofing applications (not recommended roofs that exceed 250°F (121°C) operating temperature).

Not recommended for use on roof slopes less than 2"/12" (without approval).

Not recommend for use over granulated surfaces or existing roof coverings.

## SHELF LIFE

**Rainproof 60** maintains optimum initial adhesion to substrates when used within one year from the date of manufacture.

## STORAGE

**Rainproof 60** should be stored in the original, unopened container at ambient temperatures between 40°F to 90°F (5°C to 32°C). Storage area should remain dry and out of direct sunlight. Do not remove materials from original containers until ready for use. Do not double stack pallets. Do not store rolls on end.

## **PREPARATION**

Roof deck surface shall be clean, dry and free of any foreign materials. The roof deck surface shall be free of gaps, sharp edges and protrusions.

\* Note: If deck surface cannot be cleaned to a like new surface or the deck is damp or below 40°F (4°C), primer should be used prior to the application of the membrane. Refer to: Technical Letter Primer Selection for more information.

## **APPLICATION**

**Rainproof 60** can be installed on any exterior grade solid sheathing normally used for roof decking. Install membrane such that all laps shed water in both vertical and horizontal installations.

Valleys require a minimum 18" wide roll of **Rainproof 60**, centered down the full length of the valley. Install membrane starting at the lowest point of roof slope and work up the slope.

Position the roll into the desired location, roll out the membrane and cut to length as needed.

Align the roll with edge of eave or overlap of preceding roll, pull membrane tight, start by removing a portion of the 2½" zip strip release liner and adhere to roof deck (reposition as needed prior to removing the remaining release liner).

Lift the opposing end of the membrane and remove or strip the release liner, pulling it to one side, keep membrane aligned and tight, adhere membrane to the roof deck while another person brooms the sheet flat.

Edge laps are 2" minimum and end laps are 6" minimum. All laps should be firmly pressed or rolled to ensure a positive seal.

\* Additional methods and details can be found at [www.protectowrap.com](http://www.protectowrap.com).

## **CLEAN UP**

Dispose of waste in accordance to local requirements. Control worksite so that boxes and release liner do not present a hazard.

Packaging materials and release liner can be recycled.

## **CAUTION**

**Rainproof 60** should not come into contact with solvent based products, polysulfide's, plasticized PVC roofing materials or high concentrations of resins (pitch).

**Rainproof 60** incorporates a slip resistant surface; however, Protecto Wrap Company recommends the use of appropriate fall protection when installing roof underlayments.

## **LIMITED WARRANTY**

This product is covered by the Protecto Wrap Standard 10 Year Limited Warranty.

PROTECTO WRAP COMPANY  
1955 South Cherokee Street  
Denver, CO 80223  
(303) 777-3001 • (800) 759-9727  
FAX (303) 777-9273  
[www.protectowrap.com](http://www.protectowrap.com)