



# Protecto Wicking Fabric™

## Window Sill Pan System

### TECHNICAL DATA

Properties	Test Method	Test Results
Color		Black wicking membrane
Air infiltration	ASTM E283-99	<0.01cfm Passed
Water penetration	ASTM E547	7.50 psf
Water penetration	ASTM E331	7.50 psf
Operating Temperature		40°F to 120°F (4°C to 49°C)

### PACKAGING

4" x 50' roll

8" x 50' roll

### DESCRIPTION

**Protecto Wicking Fabric** combines our aggressive butyl hybrid adhesive with an advanced waterproofing/wicking membrane to evacuate incidental moisture to the exterior weather plane of the structure.

### FEATURES

- Forms a waterproof barrier under windows
- Can be custom fitted and cut to accommodate any window opening
- Easy Installation
- Advanced Wicking membrane captures and evacuates water to the exterior

### USES

**Protecto Wicking Fabric** is used as a sill pan system under windows to evacuate incidental moisture from within the rough opening to the exterior weather plane of the building.

### LIMITATIONS

Not recommended for use sliding doors, entry doors or swing doors. Contact Protecto Wrap Company Technical Representative for application recommendations.

### SHELF LIFE

**Protecto Wicking Fabric** maintains optimum initial adhesion to substrates when used within one year from the date of manufacture.

### STORAGE

**Protecto Wicking Fabric** should be stored in the original, unopened container at ambient temperatures between 40°F to 90°F (5°C to 32°C). Storage area should remain dry and out of direct sunlight. Do not remove materials from original containers until ready for use. Do not double stack pallets.

### PREPARATION

Rough opening surfaces shall be clean, dry and free of any foreign materials. The rough opening surfaces shall be free of gaps, sharp edges and protrusions.

\* If rough opening surfaces cannot be cleaned to a like new surface, damp or below 40°F (5°C), primer should be used prior to the application of the membrane. Refer to: Technical Letter Primer Selection for more information.

**APPLICATION**

Please contact a Protecto Wrap Company Technical Advisor for specific instructions and applications at 800-759-9727

**CLEAN UP**

Dispose of waste in accordance to local requirements. Control worksite so that boxes and release liner do not present a hazard.

Packaging materials and release liner can be recycled.

**CAUTION**

**Protecto Wicking Fabric** should not come into contact with solvent based products, polysulfide's, plasticized PVC products or high concentrations of resins (pitch).

**LIMITED WARRANTY**

This product qualifies for the Protecto Wrap Company 15 Year Warranty when used as a complete system. Contact Protecto Wrap Company Technical Advisor for more information.

PROTECTO WRAP COMPANY  
1955 South Cherokee Street  
Denver, CO 80223  
(303) 777-3001 • (800) 759-9727  
FAX (303) 777-9273  
[www.protectowrap.com](http://www.protectowrap.com)