# **SAFETY DATA SHEET**

This SDS complies with 29 CFR 1910.1200 (OSHA Hazard Communication Standard) and Canadian WHMIS Regulations.

IMPORTANT: Read this SDS before handling and disposing of this product.

Pass this information on to employees, customers, and users of this product.

#### 1. PRODUCT AND COMPANY IDENTIFICATION

Product Identity: Flat Flash (05\_2020)

Intended Use: Construction Waterproofing Material

Manufacturer:Protecto Wrap CompanyTelephone:(303) 777-30011955 South Cherokee StreetFax:(303) 777-9273

Denver, CO 80223 Internet: www.protectowrap.com

**Emergency Phone**: ChemTel: Domestic 800-255-3924, International 813-248-0585, Mexico 800-099-0731

Prepared by: Protecto Wrap Company, 1955 S Cherokee St., Denver, CO 80223 (800) 759-9727

## 2. HAZARDS IDENTIFICATION

This product is a solid tape (one side black, the other white) without odor. Product is not flammable but will burn under fire conditions. May cause mild eye and skin irritation. However, it is a manufactured article as defined in 29 CFR 1200(c) and not considered to be hazardous when used/applied per manufacturer's guidelines.

# 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### Hazardous

Hazardous Component Subcomponen	t CAS No.	<u>Amount</u>	<b>Exposure Limit</b>
Asphalt (petroleum; bitumen)	8052-42-4	50-80%	0.5 mg/m3 TLV-TWA
Calcium Carbonate	1317-65-3	10-20%	5 mg/m3 PEL-TWA (respirable fraction)
			10 mg/m3 TLV-TWA

Non-Hazardous Components >1%: Resins and Polymers 10-30%;

#### 4. FIRST AID MEASURES

**EYE:** First check victim for contact lenses and remove if present. Flush victim's eyes with large quantities of water, holding the eyelids apart. Get medical attention.

**SKIN:** Remove contaminated clothing and launder before re-use. Wash skin thoroughly with soap and water. If rash or irritation develop, get medical attention. (Discard contaminated shoes)

**INGESTION:** If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. **DO NOT** induce vomiting unless directed by medical personnel. Get medical attention.

**INHALATION:** If symptoms of exposure develop, remove victim to fresh air. If breathing is difficult or symptoms persist, get immediate medical attention.

# 5. FIRE FIGHTING MEASURES

Extinguishing	Use foam or dry chemical to extinguish fire; fog nozzles if water is used. Water streams may cause		
Media	violent eruptions spreading burning product. Use water to cool fire exposed containers and structures		
Unusual Fire or	Product will burn if exposed to elevated temperatures or fire. Hot asphalt may ignite flammable		
Explosion	mixtures on contact. Toxic vapors including hydrogen sulfide may be released upon combustion.		
Hazards	Hydrog	gen sulfide vapors are heavier than air, may accumulate in low areas and flashback if ignited.	
Special Fire-Fight	ing	Firefighters should wear positive pressure self-contained breathing apparatus and full	
Instructions		protective clothing. Do not allow run-off from firefighting to enter drains or water courses	
Hazardous Comb	ustion	Carbon monoxide, sulfur oxides, hydrogen sulfide, acrolein, aldehydes, benzaldehydes,	
Products		ketones, and unidentified organic compounds may be formed on combustion.	

Explosion Data (sensitivity to mechanical impact or static discharge)

None Known

# 6. ACCIDENTAL RELEASE MEASURES

Wear appropriate protective clothing as described in Section 8. Pick up and place into an appropriate container for disposal. If product becomes molten, allow product to cool before picking or scraping up. Report releases as required by local, state, and federal authorities.

#### 7. HANDLING AND STORAGE

**HANDLING:** Avoid contact with the eyes and skin. This product is not intended to be heated. If product is heated provide adequate ventilation and avoid breathing vapors and mists. Wash with soap and water after use.

**Do not** cut, drill, grind, or weld on or near containers, even empty containers. Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

STORAGE: Store in a cool, well ventilated area away from excessive heat and sources of ignition.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**EXPOSURE GUIDELINES:** Refer to Section 3

**ENGINEERING CONTROLS:** General ventilation should be adequate for normal use. For operations where the TLV (Threshold Limit Value) may be exceeded, mechanical ventilation such as local exhaust may be needed to maintain exposure levels below applicable limits.

**RESPIRATORY PROTECTION:** For situations where the product is heated, hydrogen sulfide may be released. In such conditions, a NIOSH approved positive pressure self-contained breathing apparatus is recommended. Air purifying respirators are not recommended for hydrogen sulfide due to its poor odor warning properties. Equipment selection depends on containment type and concentration, select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

**SKIN PROTECTION:** Avoid skin contact. Wear appropriate impervious gloves.

**LEL** & **UEL**: none determined

**EYE PROTECTION:** Safety glasses or goggles should be worn where contact is possible. Contact lenses are not recommended when using this product

OTHER: Wear impervious long-sleeved shirt and long pants to avoid skin contact. Wash thoroughly after handling

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Octanol/Water Coefficient Appearance/ Odor Solid tape (black side/white/side) without odor No data available **Auto Ignition** None Determined Not applicable **Boiling Point** Not applicable **Relative Density** Not applicable **Bulk Density** 15.723 pounds/gallon Solubility in Water Insoluble **Decomposition Temperature** Not applicable Specific Gravity 1.883 **Evaporation Rate** Not applicable **Vapor Density** Not applicable **Flammability** Burns at high temperatures Vapor Pressure Not applicable

Viscosity

**VOC Content** 

Not applicable

0%

Flash Point >320° F

Melting Point 220°F (104°C) (Softening Point)

## **10. STABILITY AND REACTIVITY**

**Flammable Limits** 

**STABILITY:** Stable under normal storage and handling conditions. **INCOMPATIBILITY:** Strong oxidizers. Avoid water if product is molten.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, sulfur oxides, hydrogen sulfide, acrolein, aldehydes,

benzaldehydes, ketones, and unidentified organic compounds.

HAZARDOUS POLYMERIZATION: Will not occur.

# 11. TOXICOLOGICAL INFORMATION

**INGESTION:** No adverse effects are expected from normal use. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

**INHALATION:** No adverse effects expected at ambient temperatures. Vapors released from heating product may cause respiratory irritation. At elevated temperatures hydrogen sulfide may be released. The release of hydrogen sulfide gas in various concentrations may cause irritation of the eyes and respiratory tract, headache, dizziness, nausea, and drowsiness. Exposure to high concentrations of hydrogen sulfide can cause respiratory arrest and death.

**EYE:** May cause irritation with redness, tearing and blurred vision. Contact with product at elevated temperatures may cause thermal burns.

**SKIN:** May cause irritation, defatting of the skin and dermatitis. Contact with product at elevated temperatures may cause thermal burns.

**SENSITIZATION:** This product is not expected to cause sensitization.

**CHRONIC/CARCINOGENICITY:** No adverse effects expected at ambient temperatures. Prolonged inhalation of asphalt smoke has been shown to cause bronchitis, pneumonitis, and abscess formation in laboratory animals. Asphalt fume

condensates have been shown to cause tumorigenic responses when repeatedly applied to the skin of laboratory animals. Prolonged inhalation of talc dust may cause lung damage (pulmonary fibrosis), however, the talc in this product is bound in a polymer matrix and dust exposure would not be expected. Asphalt (petroleum, bitumen) is listed by IARC as "Possibly Carcinogenic to Humans", Group 2B.

**MUTAGENICITY**: No adverse effects from available data. **SYNERGISTIC PRODUCTS**: None specifically known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Employees with pre-existing skin and respiratory disorders may be

at increased risk from exposure.

**ACUTE TOXICITY VALUES:** 

Asphalt: Oral Rat LD50 - >5.0 g/kg Calcium Carbonate: No data available

Skin Rabbit LD50 - > 2.0 g/kg Skin Rabbit LD50 - 14100 uL/kg

#### 12. ECOLOGICAL INFORMATION (non-mandatory)

No ecotoxicity data is available for this product at this time.

# 13. DISPOSAL CONSIDERATIONS (non-mandatory)

Dispose in accordance with local, state, and federal environmental regulations.

# 14. TRANSPORT INFORMATION (non-mandatory)

# **DOT HAZARDOUS MATERIALS DESCRIPTION**

Proper Shipping Name: Not Regulated Hazard Class/Packing Group: None UN Number: None Labels Required: None

# 15. REGULATORY INFORMATION (non-mandatory)

CERCLA / SUPERFUND	This product is not subject to CERCLA reporting requirements.		
SARA Hazard Category	(311/312) Acute Health, Chronic Health		
SARA 313 Information	This product contains the following chemicals subject to Annual Release Reporting Requirements Under SARA Title III, Section 313 (40 CFR 372):		
<b>EPA TSCA Inventory</b>	All of the ingredients in this product are listed on the EPA TSCA Inventory		
California This product contains the following chemicals known to the State of California to cause			
Proposition 65 cance	r, developmental toxicity (birth defects), or male reproductive toxicity	None	
Canada This product h	has been classified under the CPR. This SDS discloses information required by the CP	R.	
Canadian WHMIS Classi	ification Not a controlled product (manufactured article)		
Canadian CEPA	All the components of this product are listed on the Canadian DSL		
Australian NICNAS	This chemical can beimportedfor commercial purposes		

# **16. OTHER INFORMATION**

**NFPA RATING:** Health = 1 Fire = 1 Reactivity = 0 **HMIS RATING:** Health = 1<sup>i</sup> Fire = 1 Reactivity = 0 **NOTICE** - The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control and therefore, users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their purposes and they assume all risks of their use, handling and disposal of the product. Users also assume all risks regarding the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein and does not relate to its use in combination with any other material or process

<sup>&</sup>lt;sup>i</sup> See Section 11 – Toxicological Information