SAFETY DATA SHEET

This SDS complies with 29 CFR 1910.1200 (OSHA Hazard Communication Standard) and Canadian WHMIS Regulations. IMPORTANT: Read this SDS before handling and disposing of this product. Pass this information on to employees, customers, and users of this product.

1. PRODUCT AND COMPANY IDENTIFICATION					
Product Identity: Insul-Seal-50 Asphalt (06_2020) Intended Use: Construction Waterproofing Material					
Manufacturer:	Protecto Wrap Company	Telephone:	(303) 777-3001		
	1955 South Cherokee Street	Fax:	(303) 777-9273		
	Denver, CO 80223	Internet:	www.protectowrap.com		
Emergency Phone: ChemTel: Domestic 800-255-3924, International 813-248-0585, Mexico 800-099-0731					
Prepared by: Protecto Wrap Company, 1955 S Cherokee St., Denver, CO 80223 (800) 759-9727					

2. HAZARDS IDENTIFICATION

This product is a black adhesive on black membrane without odor. May cause mild eye and skin irritation. Product is not flammable but will burn under fire conditions. However, it is a manufactured article as defined in 29 CFR 1200(c) and not considered hazardous when used/applied per manufacturer's guidelines.

3. COMPOSITION/INFORMA	MATION ON INGREDIENTS			
	<u>Hazardous</u>			
<u>Hazardous Component</u>	<u>Subcomponent</u>	CAS No.	<u>Amount</u>	<u>Exposure Limit</u>
Asphalt (petroleum; bitume	n)	8052-42-4	60-80%	0.5 mg/m3 TLV-TWA
Calcium Carbonate		1317-65-3	10-20%	5 mg/m3 PEL-TWA (respirable fraction) 10 mg/m3 TLV-TWA

Non-Hazardous Components >1%: Resins and Polymers 10-30%;

4. FIRST AID MEASURES

EYE: First check victim for contact lenses and remove if present. Flush victim's eyes with large quantities of water, holding the eyelids apart. Get medical attention.

SKIN: Remove contaminated clothing and launder before re-use. Wash skin thoroughly with soap and water. If rash or irritation develop, get medical attention. (Discard contaminated shoes)

INGESTION: If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. DO NOT induce vomiting unless directed by medical personnel. Get medical attention.

INHALATION: If symptoms of exposure develop, remove victim to fresh air. If breathing is difficult or symptoms persist, get immediate medical attention.

5. FIRE FIGHTING MEASURES				
Extinguishing Media	Use foam or dry chemical to extinguish fire; fog nozzles if water is used. Water streams may cause violent eruptions spreading burning product. Use water to cool fire exposed containers and structures			
Unusual Fire or Explosion Hazards	mixture	Product will burn if exposed to elevated temperatures or fire. Hot product may ignite flammable mixtures on contact. Toxic vapors including hydrogen sulfide may be released upon combustion. Hydrogen sulfide vapors are heavier than air, may accumulate in low areas and flashback if ignited.		
Special Fire-Fighting Firefighters should wear positive pressure self-contained breathing app		Firefighters should wear positive pressure self-contained breathing apparatus and full protective clothing. Do not allow run-off from firefighting to enter drains or water courses		
Hazardous Combustion Products		Carbon monoxide, sulfur oxides, hydrogen sulfide, acrolein, aldehydes, benzaldehydes, ketones, and unidentified organic compounds may be formed on combustion.		
Explosion Data (sensitivity	y to mechanical impact or static discharge) None Known		

Explosion Data (sensitivity to mechanical impact or static discharge)

6. ACCIDENTAL RELEASE MEASURES

Wear appropriate protective clothing as described in Section 8. Pick up and place into an appropriate container for disposal. If product becomes molten, allow product to cool before picking or scraping up. Report releases as required by local, state, and federal authorities.

7. HANDLING AND STORAGE

HANDLING: Wear protective clothing/equipment as described in Section 8. Avoid contact with the eyes and skin. If product is heated provide adequate ventilation. Avoid breathing vapors, mists, dust, or fumes. Wash with soap and water after use. Remove duty clothing and lauder before reuse.

Do not cut, drill, grind, or weld on or near containers, even empty containers. Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

STORAGE: Store in a cool, well ventilated area away from excessive heat and sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES: Refer to Section 3

ENGINEERING CONTROLS: General ventilation should be adequate for normal use. For operations where the TLV (Threshold Limit Value) may be exceeded, mechanical ventilation such as local exhaust may be needed to maintain exposure levels below applicable limits.

RESPIRATORY PROTECTION: For situations where the product is heated, hydrogen sulfide may be released. In such conditions, a NIOSH approved positive pressure self-contained breathing apparatus is recommended. Air purifying respirators are not recommended for hydrogen sulfide due to its poor odor warning properties. Equipment selection depends on containment type and concentration, select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

SKIN PROTECTION: Avoid skin contact. Wear appropriate impervious gloves.

EYE PROTECTION: Safety glasses or goggles should be worn where contact is possible. Contact lenses are not recommended when using this product

OTHER: Wear impervious long-sleeved shirt and long pants to avoid skin contact. Wash thoroughly after handling

9. PHYSICAL AND CHEMICAL PROPERTIES Appearance / Odor black adhesive on black membrane without odor **Octanol/Water Coefficient** No data available Ph Autoignition None Determined Not applicable **Boiling Point** Not applicable **Relative Density** Not applicable Solubility in Water Insoluble **Bulk Density** 10.56 pounds/gallon **Decomposition Temperature** Not applicable **Specific Gravity** 1.3 Not applicable Vapor Density Not applicable **Evaporation Rate** Flammability Liquid/vapors flammable Vapor Pressure Not applicable **Flammable Limits** LEL & UEL none determined Viscosity Not applicable **Flash Point** >320° F **VOC Content** 0% None determined **Melting Point**

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage and handling conditions.

INCOMPATIBILITY: Strong oxidizers. Avoid water if product is molten.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, sulfur oxides, hydrogen sulfide, acrolein, aldehydes, benzaldehydes, ketones, and unidentified organic compounds.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

INGESTION: No adverse effects are expected from normal use. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

INHALATION: No adverse effects expected at ambient temperatures. Vapors released from heating product may cause respiratory irritation. At elevated temperatures hydrogen sulfide may be released. The release of hydrogen sulfide gas in various concentrations may cause irritation of the eyes and respiratory tract, headache, dizziness, nausea, and drowsiness. Exposure to high concentrations of hydrogen sulfide can cause respiratory arrest and death.

EYE: May cause irritation with redness, tearing and blurred vision. Contact with product at elevated temperatures may cause thermal burns.

SKIN: May cause irritation, defatting of the skin and dermatitis. Contact with product at elevated temperatures may cause thermal burns.

SENSITIZATION: This product is not expected to cause sensitization.

Insul-Seal-50 Asphalt (06_2020)

CHRONIC/CARCINOGENICITY: No adverse effects expected at ambient temperatures. Prolonged inhalation of smoke has been shown to cause bronchitis, pneumonitis, and abscess formation in laboratory animals. Fume condensates have been shown to cause tumorigenic responses when repeatedly applied to the skin of laboratory animals. Prolonged inhalation of talc dust may cause lung damage (pulmonary fibrosis), however, the talc in this product is bound in a polymer matrix and dust exposure would not be expected. Asphalt/Butyl (petroleum, bitumen) is listed by IARC as "Possibly Carcinogenic to Humans", Group 2B.

MUTAGENICITY: No adverse effects from available data.

SYNERGISTIC PRODUCTS: None specifically known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Employees with pre-existing skin and respiratory disorders may be at increased risk from exposure.

Asphalt: Oral Rat LD50 - >5.0 g/kg Skin Rabbit LD50 - > 2.0 g/kg Skin Rabbit LD50 - 14100 uL/kg Calcium Carbonate:

No data available

12. ECOLOGICAL INFORMATION (non-n	nandatory)
-----------------------------------	------------

No ecotoxicity data is available for this product at this time.

13. DISPOSAL CONSIDERATIONS (non-mandatory)

Dispose in accordance with local, state, and federal environmental regulations.

|--|

DOT HAZARDOU	S MATERIALS DESCRIP	TION			
Proper Shipping I	Name: Not Regu	lated	Hazard Class/Packing Group	: None	
UN Number:	JN Number: None Labels Required: None				
North American E	Emergency Response G	uidebook Number	None		
15. REGULATORY	NFORMATION (non-ma	andatory)			
CERCLA / SUPERF	UND This pr	roduct is not subject	to CERCLA reporting requirer	ments.	
SARA Hazard Cat	egory (311/312)	Acute Health, Chi	ronic Health		
SARA 313	A 313 This product contains the following chemicals subject to Annual Release Reporting				Nees
Information Requirements Under SARA Title III, Section 313 (40 CFR 372):				None	
EPA TSCA Invent	ory All listed in	gredients in this pro	oduct are on the EPA TSCA Inv	entory	
California	This product contair	ns the following che	micals known to the State of C	California to	None
Proposition 65	cause cancer, devel	opmental toxicity (b	irth defects), or male reprodu	ctive toxicity	None
Canada This	product has been class	ified under the CPR.	This SDS discloses informatio	n elements requ	ired by the CPR.
Canadian WHMIS	6 Classification	Not a contro	lled product (manufactured a	rticle)	
Canadian CEPA	All the components of	of this product are li	sted on the Canadian DSL. All	the components	of this product
	are listed on the Can	adian DSL (Domestic	Substances List) or Non-DSL.	It contains Silic	a (quartz) listed
	the HPA Ingredient D	isclosure List.			
Australian NICNA	S This ch	nemical can beimp	ortedfor commercial purpos	ses	
16. OTHER INFOR	MATION				

NFPA RATING: Health = 1 Fire = 1 Reactivity = 0 **HMIS RATING:** Health = 1ⁱ Fire = 1 Reactivity = 0 **NOTICE-** The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control and therefore, users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks regarding the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein and does not relate to its use in combination with any other

material or process.

ⁱ See Section 11 – Toxicological Information