SAFETY DATA SHEET

This SDS complies with 29 CFR 1910.1200 (OSHA Hazard Communication Standard) and Canadian WHMIS Regulations. IMPORTANT: Read this SDS before handling and disposing of this product. Pass this information on to employees, customers, and users of this product.

Product Identity: Premium Energy Plate Liner (06_2020) Intended Use: Construction Waterproofing Material					
Manufacturer:	Protecto Wrap Company	Telephone:	(303) 777-3001		
	1955 South Cherokee Street	Fax:	(303) 777-9273		
	Denver, CO 80223	Internet:	www.protectowrap.com		
Emergency Phone: ChemTel: Domestic 800-255-3924, International 813-248-0585, Mexico 800-099-0731					
Prepared by: Protecto Wrap Company, 1955 S Cherokee St., Denver, CO 80223 (800) 759-9727					

2. HAZARDS IDENTIFICATION

This product is a black, opaque, sticky solid with a white or colored foam layer without odor. Product is not flammable but will burn under fire conditions. May cause mild eye and skin irritation. Contact with heated product may cause thermal burns. Inhalation of vapors from heated product may cause irritation of the nose, throat, and respiratory system. However, it is a manufactured article as defined in 29 CFR 1200(c) and not considered to be hazardous when used/applied per manufacturer's guidelines.

3. COMPOSITION/INFORMATION ON INGREDIENTS							
Hazardous Sub-							
Hazardous Compo	onent	<u>component</u>	CAS No.	<u>Amount</u>	Exposure Limit		
Asphalt (petroleur	m; bitume	en)	8052-42-4	25-60%	0.5mg/m ³ TLV-TWA		
Calcium Carbonat	e		1317-75-3	5-16%	5 mg/m ³ PEL-TWA (respirable fraction)		
					10mg/m ³ TLV-TWA		
Non-Hazardous C	omponer	ts >1%: Resins and Poly	mers 3-20%, P	olyethylene	(9002-88-4) 20-40%		
4. FIRST AID MEAS	URES						
EYE: First check v	ictim for o	contact lenses and remo	ve if present.	Flush victim	's eyes with large quantities of water,		
holding the eyelid	s apart. G	iet medical attention.					
		-			thoroughly with soap and water. If rash or		
	-	cal attention. (Discard o					
					buth to an unconscious or convulsing person.		
	DO NOT induce vomiting unless directed by medical personnel. Get medical attention.						
			emove victim t	o fresh air. I	f breathing is difficult or symptoms persist,		
get immediate me	edical atte	ention.					
5. FIRE FIGHTING N	/IEASURES	5					
Extinguishing	Use foai	n or dry chemical to ext	inguish fire; fo	g nozzles if	water is used. Water streams may cause		
Media violent eruptions spreading burning product. Use water to		o cool fire exposed containers and structures					
Unusual Fire or	Unusual Fire or Product will burn if exposed to elevated temperatures or fire. Hot product may ignite flammable		fire. Hot product may ignite flammable				
Explosion	Explosion mixtures on contact. Toxic vapors including hydrogen sulfide may be released upon combustion.			de may be released upon combustion.			
Hazards	Azards Hydrogen sulfide vapors are heavier than air, may accumulate in low areas and flashback if ignited.						
Special Fire-Fighti	ing	Firefighters should wea	fighters should wear positive pressure self-contained breathing apparatus and full				
Instructions		protective clothing. Do	not allow run-off from firefighting to enter drains or water courses				
Hazardous Combustion		Carbon monoxide, su	lfur oxides, hy	/drogen sulfi	fide, acrolein, aldehydes, benzaldehydes,		

 Products
 ketones, and unidentified organic compounds may be formed on combustion.

Explosion Data (sensitivity to mechanical impact or static discharge)

None Known

6. ACCIDENTAL RELEASE MEASURES

Wear appropriate protective clothing as described in Section 8. Pick up and place into an appropriate container for disposal. If product becomes molten, allow product to cool before picking or scraping up. Report releases as required by local, state, and federal authorities.

7. HANDLING AND STORAGE

HANDLING: Wear protective clothing/equipment as described in Section 8. Avoid contact with the eyes and skin. If product is heated provide adequate ventilation. Avoid breathing vapors, mists, dust, or fumes. Wash with soap and water after use. Remove duty clothing and lauder before reuse.

Do not cut, drill, grind, or weld on or near containers, even empty containers. Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

STORAGE: Store in a cool, well ventilated area away from excessive heat and sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES: Refer to Section 3

ENGINEERING CONTROLS: General ventilation should be adequate for normal use. For operations where the TLV (Threshold Limit Value) may be exceeded, mechanical ventilation such as local exhaust may be needed to maintain exposure levels below applicable limits.

RESPIRATORY PROTECTION: For situations where the product is heated, hydrogen sulfide may be released. In such conditions, a NIOSH approved positive pressure self-contained breathing apparatus is recommended. Air purifying respirators are not recommended for hydrogen sulfide due to its poor odor warning properties. Equipment selection depends on containment type and concentration, select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

SKIN PROTECTION: Avoid skin contact. Wear appropriate impervious gloves.

EYE PROTECTION: Safety glasses or goggles should be worn where contact is possible. Contact lenses are not recommended when using this product

OTHER: Wear impervious long-sleeved shirt and long pants to avoid skin contact. Wash thoroughly after handling

9. PHYSICAL AND CHEMICAL PROPERTIES					
Appearance/	Black/opaque, sticky solid with white /colored	Octanol/Water	No data available		
Odor	foam layer without odor	Coefficient			
Auto Ignition	Not determined	рН	Not applicable		
Boiling Point	Not applicable	Relative Density	Not applicable		
Bulk Density	Not applicable	Solubility in Water	Insoluble		
Decomposition	Temperature Not applicable	Specific Gravity	>1.0		
Evaporation Ra	ite Not Applicable	Vapor Density	Not applicable		
Flammability	Burns at high temperatures	Vapor Pressure	Not applicable		
Flammable Lim	its LEL & UEL: Not applicable	Viscosity	Not applicable		
Flash Point	>320° F	VOC Content	0%		
Melting Point	220° f (104°c) (Softening Point)				

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage and handling conditions.

INCOMPATIBILITY: Strong oxidizers. Avoid water if product is molten.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, sulfur oxides, hydrogen sulfide, acrolein, aldehydes, benzaldehydes, ketones, and unidentified organic compounds.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

INGESTION: No adverse effects are expected from normal use. Swallowing may cause gastrointestinal irritation, nausea, vomiting, and diarrhea.

INHALATION: No adverse effects expected at ambient temperatures. Vapors released from heating product may cause respiratory irritation. At elevated temperatures hydrogen sulfide may be released. The release of hydrogen sulfide gas in various concentrations may cause irritation of the eyes and respiratory tract, headache, dizziness, nausea, and drowsiness. Exposure to high concentrations of hydrogen sulfide can cause respiratory arrest and death.

EYE: May cause irritation with redness, tearing, and blurred vision. Contact with product at elevated temperatures may cause thermal burns. Dust may cause mechanical irritation.

SKIN: May cause irritation, defatting of the skin and dermatitis. Contact with product at elevated temperatures may cause thermal burns.

SENSITIZATION: This product is not expected to cause sensitization.

CHRONIC/CARCINOGENICITY: No adverse effects expected at ambient temperatures. Prolonged inhalation of Asphalt/Butyl smoke has been shown to cause bronchitis, pneumonitis, and abscess formation in laboratory animals. Fume condensates have been shown to cause tumorigenic responses when repeatedly applied to the skin of laboratory animals. Prolonged inhalation of talc dust may cause lung damage (pulmonary fibrosis), however, the talc in this

product is bound in a polymer matrix and dust exposure would not be expected. Asphalt/Butyl (petroleum, bitumen) is listed by IARC as "Possibly Carcinogenic to Humans", Group 2B.

MUTAGENICITY: No adverse effects from available data.

SYNERGISTIC PRODUCTS: None specifically known.

be at increa	CONDITIONS AGGRAVATED BY EXPOSURE: Er ased risk from exposure. KICITY VALUES:	mployees with pre-existing skin and respiratory disorders					
Asphalt:	Oral Rat LD50 - >5.0 g/kg Skin Rabbit LD50 - > 2.0 g/kg Skin Rabbit LD50 – 14100 uL/kg	Calcium Carbonate:	No data available				
12. ECOLOG	12. ECOLOGICAL INFORMATION (non-mandatory)						
No ecotoxicity data is available for this product currently							
12 DISDOSAL CONSIDERATIONS (non-mondeten)							

13. DISPOSAL CONSIDERATIONS (non-mandatory)

Dispose in accordance with local, state, and federal environmental regulations.

DOT HAZARDOUS MATERIALS DESCRIPTION					
Proper Shipping Name:	Not Regulated	Hazard Class/Packing Group:	None		
UN Number:	None	Labels Required:	None		
North American Emergency	Response Guidebook Number	None			

15. REGULATORY INFORMATION (non-mandatory)

	· · · · · · · · · · · · · · · · · · ·		
CERCLA / SUP	RFUND This product is not subject to CERCLA reporting requirements.		
SARA Hazard	ategory (311/312) Acute Health, Chronic Health		
SARA 313	This product contains the following chemicals subject to Annual Release Reporting		
Information	Requirements Under SARA Title III, Section 313 (40 CFR 372):	None	
EPA TSCA Inve	htory All listed ingredients in this product are on the EPA TSCA Inventory		

	EPA ISCA Inventor	All listed ingredients in this product are on the EPA TSCA inventory	
California Proposition 65		This product contains the following chemicals known to the State of California to None	
		cause cancer, developmental toxicity (birth defects), or male reproductive toxicity	None
	Canada This pro	oduct has been classified under the CPR. This SDS discloses information elements requir	ed by the CPR.
		· · · · · · · · · · · · · · · · · · ·	

Canadian WHMIS ClassificationNot a controlled product (manufactured article)Canadian CEPAAll the components of this product are listed on the Canadian DSL.

Australian NICNAS This chemical can be...imported...for commercial purposes

16. OTHER INFORMATION

NFPA RATING: Health = 1 Fire = 1 Reactivity = 0 **HMIS RATING:** Health = 1ⁱ Fire = 1 Reactivity = 0 **NOTICE-** The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control and therefore, users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their purposes and they assume all risks of their use, handling, and disposal of the product. Users also assume all risks regarding the publication or use of, or reliance upon, information contained herein. This information relates only to the product designated herein and does not relate to its use in combination with any other

material or process.

ⁱ See Section 11 – Toxicological Information