



PROTECTO DECK™

Waterproof Membrane for Exterior Decks



Protecto Wrap's waterproofing membrane technology has been proven over decades and now has been updated for ease of installation on balcony tile applications

When building a deck or balcony, if not waterproofed properly, damage can occur not only to the patio but worse, the structure beneath it. Exposure to water can create leaks resulting in expensive and time-consuming repairs.

Protecto Wrap Company's Protecto Deck™ protects roof deck surfaces from costly water damage. The system's nominal 70 mil membrane, latex liquid membrane and reinforcing fabric serve as your primary roof deck waterproofing in an installer friendly application. Its peel and stick application with a fabric top coating makes an excellent bonding surface for latex modified thin-set mortars and allows for immediate installation of tile or stone. No more wasted time with complicated installation or waiting for curing.

Allows for immediate installation of tile or stone – no curing time needed

FEATURES & BENEFITS

- 30 day exposure rating
- A nominal 70 mil, fully adhered waterproofing system
- Fabric top coating makes an excellent bonding surface for latex modified thin-set mortars
- Easy to use peel and stick application
- Antimicrobial coated fabric
- No curing time needed – fabric top coating allows for immediate installation of tile or stone
- Ideal for balconies, sun decks, patios and exterior decks
- IAPMO UEL-5020 certified
- Florida Product Approval FL# 27201 and Miami Dade NOA # 18-0530.06



PROTECTO DECK™

Quick Install Guide

- 1** All exterior deck surfaces must have a minimum 1/4" per foot slope to drain and must meet current TCNA and ANSI substrate and structural standards (refer to tech data sheet or full instruction manual).



- 2** Make sure you have all of the required components, Protecto Deck membrane, Protecto LM Reinforcing Fabric, Protecto LM Liquid Membrane, primer and detail tape for any drains.



- 3** Layout and pre-cut Protecto Deck membrane.



- 4** Prime surface with #80/#1170 VOC Primer or Protecto Universal Water Based Primer and allow to dry.



- 5** Install Protecto Deck membrane.



- 6** Cut fabric to sit around all transitions, posts and protrusions.



- 7** Apply liberal coat of Protecto LM Liquid Membrane and embed Protecto LM Reinforcing Fabric.



- 8** Re-coat with Protecto LM Liquid Membrane.



- 9** Apply liberal coat of Protecto LM Liquid Membrane to all overlap seams and ensure any exposed Protecto LM Reinforcing Fabric is coated.



- 10** Allow to dry for 24 hours. Complete a flood test.



- 11** Install tile.



Protecto Wrap Company
1955 S. Cherokee Street
Denver, CO 80223
(800) 759-9727
www.ProtectoWrap.com

