



Premium Building Products  
That Protect

**TECHNICAL DATA**

Properties	Test Results
Color	Black Facer / Black Adhesive
Thickness	35 mils ± 5 mils
Tensile Strength	400psi
Elongation	(ultimate 500% min. failure of butyl mass)
Permeance	.013 avg.
Pliability	Pass
Installation Temperature	32°F to 120°F (0°C to 48°C)
In-Service Temperature	-45°F to 300°F (-42.8°C to 148.8°C)
Nail Sealability	Pass

**PACKAGING**

Roll Size:

4" x 50' (12 rolls/case)

6" x 50' (8 rolls/case)

9" x 50' (4 rolls/case)

12" x 50' (4 rolls/case)

**DESCRIPTION**

Protecto Wrap SafSeal - 6620 Wall Flashing is a self-adhering air and moisture barrier for use on vertical and horizontal above grade substrates.

**FEATURES**

- SafSeal - 6620 can be used for, but is not limited to, the following applications:
- Sealing joints on gypsum sheathing in cavity wall construction
- Window and door flashings
- Sealing joints in exterior gypsum board sheathing
- Beneath metal cap flashing
- Applications on surfaces as cold as 32°F (0°C) or above
- All critical high-temperature applications where a moisture, vapor or air barrier is required
- 120 day exposure rating

**USES**

SafSeal - 6620 is a 35 mil thick polyethylene faced butyl adhesive membrane that can be applied to wood, gypsum board, steel, concrete, building paper, block wall, insulation board, plywood, metal, styrene and polyethylene surfaces to form a positive and immediate moisture and vapor barrier protection system. The butyl rubber compound adhesive provides excellent thermal resistance to high-temperature environments. The butyl compound adhesive has been tested and proven not to cold flow at elevated temperatures up to 300°F (149°C).

**LIMITATIONS**

Not recommend to be applied over uncured (wet) sealants or adhesives, even if compatible  
Not recommend for roofing applications.

Not recommended for use on substrates with standing water or visibly wet surfaces, dirty surfaces, frozen.

Not recommend for use on deck joists.

## SHelf LIFE

SAFSEAL- 6620 maintains optimum initial adhesion to substrates when used within one year from the date of manufacture.

## STORAGE

SAFSEAL- 6620 should be stored in a dry, well-ventilated area out of direct sunlight between 50°F (10°C) and 90°F (32°C). Do not double stack pallets. Do not store rolls on end. Do not remove from box until ready to use.

## PREPARATION

Surfaces should be clean, dry and free of dirt and other foreign matter. Surfaces must be 32°F (0°C) or above. For any application below 32°F (0°C), or excessively dusty gypsum sheathing, we recommend that the surface be primed with one of the listed primers below and depending on temperature or regional related requirements. Concrete, masonry, or retrofit surfaces to be waterproofed must be primed. The surface shall be free of gaps, sharp edges and protrusions.

## PRIMERS

Protecto Wrap Company self-adhered membranes come into contact with various substrates in many different conditions. In some cases primers are needed to ensure optimum adhesion to the substrate. Use the following guide to determine the recommended primer, mastic and sealant that can be used depending on the application.											
Primer Ref. #	Primer Name	Primer Description	Coverage per		Substrate/Surface/Primer Reference #						
			Sq. Ft.	UOM	Sheet Metal, Galvanized Metal, Steel (1)	Aluminum (1)	Vinyl	Concrete Flatwork	Concrete Vertical	Concrete Block	Dens Glass Gold <sup>o</sup>
1	#80 / 1170 VOC	Asphalt based for horizontal surfaces/substrates*	175 - 200	gal.							
3	#100 VOC	High Tack SBS based for vertical and weathered surfaces*	150 - 225	gal.							
4	BT	A moisture tolerant, high tack SBS rubber based primer for horizontal and vertical surfaces *	150	gal.							
5	Spray Tak	Aerosol Spray Can high tack adhesive intended for use on "Small Areas" (short open time)	100	13 oz. can							
8	Universal Water Base	A low VOC high tack water based primer for int. and ext. use on horizontal and vertical surfaces	250 - 350	gal.							
* Not recommended for sale or use in areas that have VOC Emission Limits of less than 300 gm/liter											
Substrate/Surface/Primer Reference #											
Membrane/Tape Product	Membrane Adhesive	Wood; Plywood; Pressure Treated; OSB	Sheet Metal, Galvanized Metal, Steel (1)	Aluminum (1)	Vinyl	Concrete Flatwork	Concrete Vertical	Concrete Block	Dens Glass Gold <sup>o</sup>	ICF	
SafSeal											
SafSeal 6626/60 Foil Tape	Butyl	1,3,8	1,3,8	1,3,8	3,4,5,8	1,3,8	-	-	-	-	
SafeSeal 6610 SeamSeal Tape	Butyl	3,4,5,8	3,4,5,8	3,4,5,8	3,4,5,9	3,4,5,8	3,4,8	3,4,8	4,8	8	
Saf Seal 6634 A&VB; TWF	Butyl	3,4,5,8	3,4,5,8	3,4,5,8	3,4,5,10	3,4,5,8	3,4,8	3,4,8	4,8	8	

(1) Metal surfaces may need to be solvent wiped and/or abraded to achieve optimum adhesion.

Metal surfaces may need to be solvent wiped and/or abraded to achieve optimum adhesion.

Note: Protecto Wrap Company recommends testing substrates for adhesion prior to full application. See Technical Letter-Adhesion to Substrates.

## APPLICATION

Cut a piece of SAFSEAL- 6620 in a length that can be easily handled. Begin the application by removing approximately 12 inches of the release paper and center the tape over the area to be sealed. Horizontal joints should be covered first, then vertical joints. Firmly press or roll the SAFSEAL- 6620 against the surface and continue pulling off the release paper while smoothing the tape into place. Roll the SAFSEAL- 6620 to ensure a tight seal and minimize trapping air beneath the tape. Membrane overlaps should be a minimum of 4".

Mechanical fasteners (i.e. staples or screws) may be used for additional attachment on the substrate, if desired. SAFSEAL- 6620 will self-seal around smooth shank fasteners. For any other fastener types please contact Protecto Wrap Company.

Housewrap materials may be coated and self-adhering tapes may not bond without the assistance of primers or adhesives. Contractors should test samples of housewraps for compatibility, and if adhesion is adequate, SAFSEAL- 6620 can be used with housewraps without the requirement of primer or adhesives.

**CLEAN UP**

Dispose of waste in accordance to local requirements. Control worksite so that boxes and release liner do not present a hazard. Packaging materials and release liner can be recycled.

**CAUTION**

SAFSEAL has an aggressive adhesive, we recommend removing 3" to 6" of the poly film release liner at a time while installing to help prevent the tape from sticking to itself.

Protecto Wrap Company recommends the use of safety glasses and gloves. Protecto Wrap Company recommends the use of appropriate fall protection when working above ground level

**LIMITED WARRANTY**

This product is covered by the Protecto Wrap Standard 10 year Limited Warranty.

PROTECTO WRAP COMPANY  
1955 South Cherokee Street  
Denver, CO 80223

(303) 777-3001 • (800) 759-9727 FAX (303) 777-9273  
[www.protectowrap.com](http://www.protectowrap.com)  
Made in U.S.A.