



# PROTECTO WALL VP™

## Self-Adhering, Self-Sealing Vapor Permeable Weather Resistive Barrier



### Roll Sizes:

**40" x 120' (400 ft<sup>2</sup>)**  
**12" x 120' (120 ft<sup>2</sup>)**

**10 Year Limited  
Warranty**

- No primer needed – utilizes Super Stick Technology Adhesive
- Fully adhered without mechanical fasteners or seam tape
- Install year round, in temperatures as cold as -20°F (-28°C) or as hot as 125°F (52°C)
- 180 day UV exposure
- Compatible with and will adhere to most construction surfaces
- Drainage Efficiency 98.5%
- NFPA 285 Compliant Assemblies

## RELATED PRODUCTS

### PROTECTO SUPER STICK BUILDING TAPE®



A high performance window and door flashing tape designed to be applied down to -20°F (-28.88°C) without the use of primer or mechanical fasteners on most substrates. Provides a full 12 month UV exposure and contains no rubberized asphalt.

### PROTECTO SILL PAN FLASH™



A custom designed one piece sill flashing tape that conforms to the rough sill to create a continuous sill pan. Completely seals sill corners to prevent water damage. Available in rubberized asphalt and butyl. Use with a Protecto Wrap Primer.

### PROTECTO SEALANT 25XL



Protecto Sealant 25XL is a high performance, one component, polyurethane sealant. It is a durable weatherproof sealant that offers excellent performance for back bedding nail flanges for window and door installation and sealing door thresholds.

### PROTECTO FORM FLASH 1



A peel and stick conformable flexible flashing tape used to seal around penetrations in walls in commercial and residential construction. Use with a Protecto Wrap Primer.

