1. PRODUCT NAME
#90 VOC Primer

2. MANUFACTURER
Protecto Wrap Co.
1955 South Cherokee St.
Denver, CO 80223
(800) 759-9727
(303) 777-3001
Fax: (303) 777-9273
E-mail: info@protectowrap.com
www.protectowrap.com

3. PRODUCT DESCRIPTION
#90 Primer is a solvent and asphalt based primer with an added corrosion inhibitor/converter for use on rusted metal surfaces. #90 primer will both eliminate existing rust and prevent future rust. It is recommended to be used in conjunction with Protecto Wrap pipe wrap and Protecto Farm products.

4. PROPERTIES

Property	Information
Adhesion to steel	Excellent
Adhesion to concrete	Excellent
Adhesion to membrane	Excellent
Shelf Life (min.)	One Year
Tack free time	15-45 minutes
Specific Gravity	0.93
% Solids (by weight)	49
Flash Point	71°F TCC

5. INSTALLATION
PREPARATION:
• The surface shall be cleaned by brooming, vacuuming or high pressure clean dry air so that all dirt, dust, loose concrete, or other contaminants that may adversely affect the adhesion of the membrane are removed.

• Thinning of the primer is not recommended.

APPLICATION:
• Apply primer to all surfaces by roller or brush.

• Primed surface shall be free of runs, puddles or excessive primer as this could cause blistering. Brush or roll out all primer puddles or drips immediately.

• Prime only as much area as can be covered in half a day's work. Re-prime areas not covered in half a day's work with a light coat of #90 Primer.

• The opened containers, when not in use, should have the lids replaced so as to lessen the evaporation of the solvents.

NOTE:
• Please wear gloves and safety glasses when handling #90 VOC Primer and be sure work area is well ventilated. Carefully clean up with mineral spirits, xylene, toluene, or acetone.

6. PACKAGING AND WEIGHTS
Quantity Packaging Weight 1 U.S. Gallon 4 gallons/carton 38 lbs. 5 U.S. Gallon pail 1 pail 46 lbs. 55 U.S. Gallon drum 1 drum 485 lbs. PROTECTO WRAP COMPANY (303) 777-3001 • (800) 759-9727 FAX (303) 777-9273 www.protectowrap.com