



PROTECTO WALL VP[®]

Self-Adhering, Self-Sealing, Drainable Vapor Permeable Water Resistive Barrier



BEST OF IBS[™]
AWARDS 2024

WINNER
MOST
INNOVATIVE
BUILDING
MATERIAL



Roll Sizes:
40" x 120' (400 ft²)
12" x 120' (120 ft²)

10 Year Limited
Warranty

- No primer needed – utilizes Super Stick Technology Adhesive
- Drainage Efficiency 98.5%
- Fully adhered without mechanical fasteners or seam tape
- Install year round, in temperatures as cold as -20°F (-28°C) or as hot as 125°F (52°C)
- 180 day UV exposure
- Compatible with and will adhere to most construction surfaces
- NFPA 285 Compliant Assemblies

PATENT PENDING

RELATED PRODUCTS

PROTECTO SUPER STICK BUILDING TAPE[®]



A high performance window and door flashing tape designed to be applied down to -20°F (-28.88°C) without the use of primer or mechanical fasteners on most substrates. Provides a full 12 month UV exposure and contains no rubberized asphalt.

PROTECTO SILL PAN FLASH[™]



A custom designed one piece sill flashing tape that conforms to the rough sill to create a continuous sill pan. Completely seals sill corners to prevent water damage. Available in rubberized asphalt and butyl. Use with a Protecto Wrap Primer.

PROTECTO SEALANT 25XL



Protecto Sealant 25XL is a high performance, one component, polyurethane sealant. It is a durable weatherproof sealant that offers excellent performance for back bedding nail flanges for window and door installation and sealing door thresholds.

PROTECTO FORM FLASH 1



A peel and stick conformable flexible flashing tape used to seal around penetrations in walls in commercial and residential construction. Use with a Protecto Wrap Primer.

