SAFETY DATA SHEET

This SDS complies with 29 CFR 1910.1200 (OSHA Hazard Communication Standard) and Canadian WHMIS Regulations. IMPORTANT: Read this SDS before handling and disposing of this product. Pass this information on to employees, customers, and users of this product.

1. PRODUCT AND	COMPANY IDENTIFICATION			
Product Identity	Product Identity: 320-35 Cold Applied Pipe Tape (09_2024) Annufacturer: Protecto Wrap Company Telephone: (303) 777-3001 Internet: Protecto Wrap Company Telephone: (303) 777-9273 Denver, CO 80223 Internet: www.protectowrap.com mergency Phone: ChemTel: Domestic 800-255-3924, International 813-248-0585, Mexico 800-099-0731			
Intended Use:	Manufacturer:Protecto Wrap CompanyTelephone:(303) 777-30011955 South Cherokee StreetFax:(303) 777-9273Denver, CO 80223Internet:www.protectowrap.com			
Manufacturer:	Protecto Wrap Company	Telephone:	(303) 777-3001	
	1955 South Cherokee Street	Fax:	(303) 777-9273	
	Denver, CO 80223	Internet:	www.protectowrap.com	
Emergency Phone: ChemTel: Domestic 800-255-3924, International 813-248-0585, Mexico 800-099-0731				
Prepared by: Pro	otecto Wrap Company, 1955 S Cherokee	St., Denver, CO 80223 (8	00) 759-9727	

2. HAZARDS IDENTIFICATION

This product is a solid tape, black on one side and white on the other with no odor. Product is not flammable but will burn under fire conditions. May cause mild eye and skin irritation. Contact with heated product may cause thermal burns. Inhalation of vapors from heated product may cause irritation of the nose, throat and respiratory system However, it is a manufactured article as defined in 29 CFR 1200(c) and not considered to be hazardous when used/applied per manufacturer's guidelines.

3. COMPOSITION/INFORMATI	COMPOSITION/INFORMATION ON INGREDIENTS				
	<u>Hazardous</u>				
Hazardous Component	Subcomponent	CAS No.	<u>Amount</u>	Exposure Limit	
Butyl (reclaimed) pads	n/a	n/a	20-40%	n/a	
Severely Solvent Refined		64741-96-4	25-35%	0.5 mg/m ³ TLV-TWA	
Heavy Naphthenic Distillat	te				
Montana Talc		14807-96-6	10-20%	5 mg/m ³ PEL-TWA (respirable fraction) 10 mg/m ³ TLV-TWA	

Non-Hazardous Components >1%: Resins and Polymers 5-45%;

4. FIRST AID MEASURES

EYE: First check victim for contact lenses and remove if present. Flush victim's eyes with large quantities of water, holding the eyelids apart. Get medical attention.

SKIN: Remove contaminated clothing and launder before re-use. Wash skin thoroughly with soap and water. If rash or irritation develop, get medical attention. (Discard contaminated shoes)

INGESTION: If conscious, rinse mouth with water. Never give anything by mouth to an unconscious or convulsing person. **DO NOT** induce vomiting unless directed by medical personnel. Get medical attention.

INHALATION: If symptoms of exposure develop, remove victim to fresh air. If breathing is difficult or symptoms persist, get immediate medical attention.

5. FIRE FIGHTING MEAS		5		
Extinguishing	Use foa	am or dry chemical to extinguish fire; fog nozzles if water is used. Water streams may cause		
Media	violent	eruptions spreading burning product. Use water to cool fire exposed containers and structures		
Unusual Fire or	Produc	oduct will burn if exposed to elevated temperatures or fire. Hot product may ignite flammable		
Explosion	mixture	es on contact. Toxic vapors including hydrogen sulfide may be released upon combustion.		
Hazards	Hydrog	Hydrogen sulfide vapors are heavier than air, may accumulate in low areas and flashback if ignited		
		Firefighters should wear positive pressure self-contained breathing apparatus and full		
		protective clothing. Do not allow run-off from firefighting to enter drains or water courses		
		Carbon monoxide, sulfur oxides, hydrogen sulfide, acrolein, aldehydes, benzaldehydes,		
		ketones, and unidentified organic compounds may be formed on combustion.		

Explosion Data (sensitivity to mechanical impact or static discharge)

6. ACCIDENTAL RELEASE MEASURES

Wear appropriate protective clothing as described in Section 8. Pick up and place into an appropriate container for disposal. If product becomes molten, allow product to cool before picking or scraping up. Report releases as required by local, state, and federal authorities.

7. HANDLING AND STORAGE

HANDLING: Wear protective clothing/equipment as described in Section 8. Avoid contact with the eyes and skin. If heated provide adequate ventilation. Avoid breathing vapors, mists, dust, or fumes. Wash with soap and water after use. Remove duty clothing and lauder before reuse.

Do not cut, drill, grind or weld on or near containers, even empty containers. Empty containers retain product residues can be hazardous. Follow all SDS precautions when handling empty containers.

STORAGE: Store in a cool, well ventilated area away from excessive heat and sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

EXPOSURE GUIDELINES: Refer to Section 3

ENGINEERING CONTROLS: General ventilation should be adequate for normal use. For operations where the TLV (Threshold Limit Value) may be exceeded, mechanical ventilation such as local exhaust may be needed to maintain exposure levels below applicable limits.

RESPIRATORY PROTECTION: For situations where the product is heated, hydrogen sulfide may be released. In such conditions, a NIOSH approved positive pressure self-contained breathing apparatus is recommended. Air purifying respirators are not recommended for hydrogen sulfide due to its poor odor warning properties. Equipment selection depends on containment type and concentration, select in accordance with 29 CFR 1910.134 and good industrial hygiene practice. For firefighting, use self-contained breathing apparatus.

SKIN PROTECTION: Avoid skin contact. Wear appropriate impervious gloves.

EYE PROTECTION: Safety glasses or goggles should be worn where contact is possible. Contact lenses are not recommended when using this product

OTHER: Wear impervious long-sleeved shirt and pants as needed to prevent contact. Wash thoroughly after handling

9. PHYSICAL AND CH	EMICAL PROPERTIES		
Appearance/Odor	Tape, black on one side/white on othe odor	er with no Octanol/Water Coefficient	No data available
Auto Ignition	Not Determined	рН	Not applicable
Boiling Point	Not applicable	Relative Density	Not Determined
Bulk Density	Not applicable	Solubility in Water	Insoluble
Decomposition Tem	perature Not applicable	Specific Gravity	>1.0
Evaporation Rate	Not Applicable	Vapor Density	Not applicable
Flammability	Not Applicable	Vapor Pressure	Not applicable
Flammable Limits	LEL & UEL: Not applicable	Viscosity	Not applicable
Flash Point	>300° F	VOC Content	0%
Melting Point	Not Determined		

10. STABILITY AND REACTIVITY

STABILITY: Stable under normal storage and handling conditions.

INCOMPATIBILITY: Strong oxidizers. Avoid water if product is molten.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, sulfur oxides, hydrogen sulfide, acrolein, aldehydes, benzaldehydes, ketones and unidentified organic compounds.

HAZARDOUS POLYMERIZATION: Will not occur.

11. TOXICOLOGICAL INFORMATION

INGESTION: No adverse effects are expected from normal use. Swallowing may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

INHALATION: No adverse effects expected at ambient temperatures. Vapors released from heating product may cause respiratory irritation. At elevated temperatures hydrogen sulfide may be released. The release of hydrogen sulfide gas in various concentrations may cause irritation of the eyes and respiratory tract, headache, dizziness, nausea and drowsiness. Exposure to high concentrations of hydrogen sulfide can cause respiratory arrest and death.

EYE: May cause irritation with redness, tearing and blurred vision. Contact with product at elevated temperatures may cause thermal burns. Dust may cause mechanical irritation.

SKIN: May cause irritation, defatting of the skin and dermatitis. Contact with product at elevated temperatures may cause thermal burns.

SENSITIZATION: This product is not expected to cause sensitization.

CHRONIC/CARCINOGENICITY: No adverse effects expected at ambient temperatures. Prolonged inhalation of Asphalt/Butyl smoke has been shown to cause bronchitis, pneumonitis, and abscess formation in laboratory animals. Asphalt/Butyl fume condensates have been shown to cause tumorigenic responses when repeatedly applied to the skin of laboratory animals. Prolonged inhalation of talc dust may cause lung damage (pulmonary fibrosis), however, the talc in this product is bound in a polymer matrix and dust exposure would not be expected. Asphalt/Butyl (petroleum, bitumen) is listed by IARC as "Possibly Carcinogenic to Humans", Group 2B.

MUTAGENICITY: No adverse effects from available data.

SYNERGISTIC PRODUCTS: None specifically known.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Employees with pre-existing skin and respiratory disorders may be at increased risk from exposure.

ACUTE TOXICITY VALUES:

No acute toxicity data available for components

12. ECOLOGICAL INFORMATION (non mandatory)

No ecotoxicity data is available for this product at this time.

13. DISPOSAL CONSIDERATIONS (non mandatory)

Dispose in accordance with local, state and federal environmental regulations.

		14.	TRANSPORT	INFORMATION	(non mandatory)
--	--	-----	-----------	-------------	-----------------

DOT HAZARDOUS	S MATERIALS DESC	RIPTION			
Proper Shipping N	Name: Not Re	gulated	Hazard Class/Packing Group:	None	
UN Number:	None		Labels Required:	None	
North American E	Emergency Response	e Guide Book Nun	nber None		
15. REGULATORY I	NFORMATION (non	mandatory)			
CERCLA / SUPERF	UND This	product is not su	bject to CERCLA reporting requirem	ents.	
SARA Hazard Cate	egory (311/312)	Acute Health,	, Chronic Health		
SARA 313 This product contains the following chemicals subject to Annual Release Re			e Reporting	None	
Information	Requirements Und	ler SARA Title III, S	Section 313 (40 CFR 372)		NOTE
EPA TSCA Invento	ory All of the	ingredients in thi	s product are listed on the EPA TSCA	Inventory	
California	This product co	ontains the follow	ing chemicals known to the State of	California to	Nono
Proposition 65 cause cancer, developmental toxicity (birth defects), o			xicity (birth defects), or male reprod	uctive toxicity	None
Canada Thi	s product has been	classified under tl	he CPR. This SDS discloses informati	on required by t	he CPR.
Canadian WHMIS	Classification	Not a co	ontrolled product (manufactured art	icle)	
Canadian CEPA		All the c	components of this product are listed	d on the Canadia	n DSL
Australian NICNA	S	This che	emical can beimportedfor comme	ercial purposes	

16. OTHER INFORMATION

NFPA RATING: Health = 1 Fire = 1 Reactivity = 0 **HMIS RATING:** Health = 1ⁱ Fire = 1 Reactivity = 0 **NOTICE** - The supplier disclaims all expressed or implied warranties of merchantability or fitness for a specific use, with respect to the product or the information provided herein, except for conformation to contracted specifications. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its accuracy or sufficiency. Conditions of use are beyond our control and therefore, users are responsible for verifying the data under their own operating conditions to determine whether the product is suitable for their purposes and they assume all risks of their use, handling and disposal of the product. Users also assume all risks regarding the publication or use of, or reliance upon, information contained herein.

This information relates only to the product designated herein and does not relate to its use in combination with any other material or process.

ⁱ See Section 11 – Toxicological Information