



# Protecto CMU100™ Water Resistant Coating



## Water Resistant Coating for Concrete and Masonry

Protecto Wrap's CMU100 is a water resistant liquid membrane coating for application to concrete and masonry. It is an advanced hybrid acrylic polymer blended coating that is both flexible and breathable and can be applied with a brush, roller or airless sprayer. The coating is odorless, dries tan and can be painted any color.



*Great for rough openings in masonry construction and replacement installations*

## FEATURES & BENEFITS

- Single component product/no additives needed
- One step application/no primer needed
- Brush or roller applied
- Excellent adhesion/bonds to multiple surfaces
- Great for new construction or replacement applications
- Water-based for easy cleanup
- Meets or exceeds ICC-ES AC29 requirements
- Seals around tough and complex areas
- Seamless adhesion
- UV stable, 90 day exposure
- 10 year warranty
- Available in 1 gallon and 5 gallon sizes



# Protecto CMU100™ Water Resistant Coating

**PREPARATION:**

Repair all structural deficiencies before applying CMU100 Water Resistant Coating. Protect areas or surfaces not to be coated, such as doors, windows and floors, prior to applying CMU100 Water Resistant Coating. Gaps and cracks less than 1/8" must be sealed with Protecto Sealant 25XL. Gaps larger than 1/8" must be repaired prior to applying CMU100 Water Resistant Coating. CMU100 Water Resistant Coating may be applied directly over uncured Protecto Sealant 25XL.

**APPLICATION:**

CMU100 may be applied with a brush or roller without dilution. Equipment cleans up with water. CMU100 Water Resistant Coating may be sprayed without dilution with an airless sprayer. Call your Protecto Wrap Representative for additional information.

**STORAGE:**

PROTECT FROM FREEZING. Store between 40°F (4°C) and 120°F (49°C) in original unopened containers out of weather and direct sunlight. If material has frozen, it will turn into a semi-solid condition and/or smell bad and should not be used.

## PROTECTO WRAP ACCESSORIES

### PROTECTO SEALANT 25XL



Protecto Sealant 25XL is a high performance, low modulus, one component, moisture curing, polyurethane sealant. It is a durable weatherproof sealant that offers excellent performance for back bedding nail flanges for window and door installation and sealing door thresholds.

### STUCCO TAPE



Protecto Wrap Stucco Tape is a superior self-adhering, air and moisture barrier for vertical and horizontal EIFS/Stucco systems. Protecto Wrap Stucco Tape is a 30 mil SBS modified rubberized asphalt membrane with a polyester top surface.

### SUPER STICK BUILDING TAPE™



A high tack, tenacious, durable, self-adhered air/vapor barrier tape system used for sealing PVC and aluminum fin windows and doors; window and door openings; and as a full coverage air vapor barrier membrane.

### DUAL GUARD THRESHOLD TAPE™



The ultimate protection from air and moisture infiltration under the threshold, Dual Guard has a unique patented flange which acts like a gasket, sealing off the sub-floor and preventing air and moisture infiltration.



Protecto Wrap Company  
1955 S. Cherokee Street • Denver, CO 80223  
(800) 759-9727 • [www.ProtectoWrap.com](http://www.ProtectoWrap.com)

