



# PROTECTO WALL VP®

**Self-Adhering, Self-Sealing, Drainable  
Vapor Permeable Water Resistive Barrier**



## Roll Sizes:

**40" x 120' (400 ft²)**  
**12" x 120' (120 ft²)**

**10 Year Limited  
Warranty -  
System Warranty  
Available**



- No primer needed – utilizes Super Stick Technology Adhesive
- Drainage Efficiency 98.5%
- Fully adhered without mechanical fasteners or seam tape
- Install year round, in temperatures as cold -20°F (-28°C) or as hot as 125°F (52°C)
- NFPA 285 Compliant Assemblies
- 180 day UV exposure, 300°F (149°C) in-service temperature
- Compatible with and will adhere to most construction surfaces

**BEST OF IBS™  
AWARDS 2024**

**WINNER  
MOST  
INNOVATIVE  
BUILDING  
MATERIAL**



PATENT PENDING

## RELATED PRODUCTS

### PROTECTO SUPER STICK BUILDING TAPE®



A high performance window and door flashing tape designed to be applied down to -20°F (-28.88°C) without the use of primer or mechanical fasteners on most substrates. Provides a full 12 month UV exposure and contains no rubberized asphalt.

### PROTECTO SEALANT 25XL



Protecto Sealant 25XL is a high performance, one component, polyurethane sealant. It is a durable weatherproof sealant that offers excellent performance for back bedding nail flanges for window and door installation and sealing door thresholds.

### PROTECTO SILL PAN FLASH™

A custom designed one piece sill flashing tape that conforms to the rough sill to create a continuous sill pan. Completely seals sill corners to prevent water damage. Available in rubberized asphalt and butyl. Use with a Protecto Wrap Primer.



### PROTECTO FORM FLASH 1

A peel and stick conformable flexible flashing tape used to seal around penetrations in walls in commercial and residential construction. Use with a Protecto Wrap Primer.

