



PROTECTO EXTREME STORM KIT™

INSTRUCTIONS FOR USE

SEAL OUT STORM SURGE & FLOOD WATER BEFORE THE HURRICANE HITS



WHAT'S INCLUDED IN YOUR KIT:

- ▶ 1 Roll of Extreme™ Tape (4" x 66')
- ▶ 2 Pieces of Extreme™ Protection Membrane (36" x 10')
- ▶ 1 Protecto Wrap Slim Pen Cutter Utility Knife
- ▶ 1 Protecto Wrap Membrane Smoother Tool
- ▶ 1 Sample of Form Flash™ Max
- ▶ 2 Tubes of Protecto Sealant 25XL

- Please Note: Protecto Sealant 25XL is designed for long term applications and is intended to remain in place.

! BEFORE YOU START

- Make sure surfaces are clean, dry, and free of dirt, dust, oil, or loose material.
- A clean surface ensures proper adhesion of all products.
- You will need a caulking gun, tape measure and gloves.
- Ideal application temperature: 40° F - 100° F (4° C - 38° C).

STEP-BY-STEP INSTRUCTIONS:

1. SEALING WINDOWS & DOORS (EXTERIOR):

Use: Extreme 4" Tape

- Cut the 4" tape to fit along the frame edges and sides as shown above.
- Peel back a couple inches of the white release liner. Align the piece of tape to your application and press the exposed adhesive section into place.
- Continue pulling off the release liner and smoothing the tape into place by hand.
- Overlap tape pieces by at least 1" where needed.
- Once the tape is securely in place, smooth it into place further with the red smoother tool that came in the kit. Smooth out wrinkles so there are no gaps between the tape and the surface you are adhering to.





PROTECTO EXTREME STORM KIT™

INSTRUCTIONS FOR USE

2. SEALING GARAGE DOOR BOTTOM OR SIDE JOINTS:

Use: 36" Extreme Protection Membrane and Extreme 4" Tape

Apply Membrane:

- Unroll the 36" wide membrane and cut to fit along the full bottom length of the door.
- Peel off the release liner and press firmly onto clean surface. Adhere the membrane 12" to 18" from the bottom of the door onto the slab or driveway. Only adhere to solid surfaces.
- Use the 4" tape to seal the outside edges of the door to the frame. It can also be used to seal panel joints above the 36" membrane application.
- The 36" wide roll can also be used for temporary roof patching.

TIP: You can also apply a strip of membrane at the garage door threshold inside the garage as a second line of defense.



3. FORM FLASH MAX (SAMPLE PIECE):

- This is included as a high-performance example of our premium flashing product.
- Use it on a small, high-risk area, such as a crack or leak-prone corner.
- It is stretchable and can be conformed to inside and outside corners.



4. PROTECTO SEALANT 25XL:

- Please Note: Protecto Sealant 25XL is a high performance weatherproof sealant designed to be left in place for long term applications. It should not be used in areas where a temporary or removable application is desired. It is paintable. It is also mold and UV resistant.
- Great for sealing holes, cracks, crevices and gaps where water can penetrate.
- Smooth the bead with a gloved finger or tool for a tight seal.



5. REMOVAL INSTRUCTIONS:

- There may be adhesive residue left on surfaces when removing the tape. Use gloves, rags and mineral spirits to remove the residue.
- Repainting of surfaces may be required if paint is lifted off with the adhesive.



! REMEMBER:

This kit is designed for temporary flood protection. Always follow official evacuation orders and safety guidance during hurricanes.

Protect your home. Protect what matters.
— The Protecto Wrap Team

PROTECTO WRAP COMPANY

1955 South Cherokee Street, Denver, CO 80223 • (800) 759-9727 • www.ProtectoWrap.com

PWSK-200 (8/7/25)