



# Protecto **COOL WHITE ROOF & GUTTER TAPE™**

**White Aluminum Flexible Flashing Tape**



**10 Year Limited  
Warranty**

- Cool White Roof & Gutter Tape is a thin-profile self-adhering tape used to seal the seams on insulated aluminum panels and repair leaking gutters, RVs, sunrooms and mobile home roofs
- Protecto Wrap's Super Stick Technology™ adhesive creates an aggressive bond that can be applied in any temperature
- UV resistant
- Contains NO ASPHALT for a clean application
- Forms a long-lasting waterproof barrier
- Fast and easy installation

**EASILY SEALS ROOF SEAMS AND GUTTERS**



## Protecto COOL WHITE ROOF & GUTTER TAPE™ White Aluminum Flexible Flashing Tape

### PREPARATION:

Surfaces shall be clean, dry, free of any foreign materials, large gaps, sharp edges and protrusions. Do not walk on surface when wet or covered with frost as there is an increase risk of injury.

Metal surfaces may need to be cleaned and/or abraded to achieve optimum adhesion. Protecto Wrap Company recommends testing substrates for adhesion prior to full application of tape.

### APPLICATION:

Can be installed on any metal or vinyl gutter.

Install tape such that all laps shed water in both vertical and horizontal installations. Install tape starting at the lowest point of roof slope and work up the slope. Peel back roughly 6" of the release liner, center over the seam, apply tape and align. Continue removing release liner as tape is unrolled into place over seam. Allow 4" to 6" overlaps between pieces of tape, if possible. Apply in shingle-like fashion so that water flows over the lap, not against it. Tape should be firmly pressed or rolled to ensure a positive seal.

### LIMITATIONS:

Not recommended for roofs that exceed 300°F (149°C) operating temperature. Not recommended for use on roof slopes less than 2" / 12" (without approval). Not recommend for use over granulated surfaces or PVC, TPO or EPDM roof coverings.

### CAUTION:

Should not come into contact with solvent based products, polysulfide's, plasticized PVC, TPO and EPDM roofing materials. Protecto Wrap Company recommends the use of appropriate fall protection when installing on roof applications.

### LIMITED WARRANTY:

This product is covered by the Protecto Wrap Standard 10 year Limited Warranty.

## RELATED PRODUCTS

### PROTECTO SEALANT 25XL



Protecto Sealant 25XL is a high performance, low modulus, one component, moisture curing, polyurethane sealant. It is a durable weatherproof sealant that offers excellent performance for back bedding nail flanges for window and door installation and sealing door thresholds.

### PROTECTO PRIMER-FREE STUCCO TAPE

A high performance tape designed for use with stucco and EIFS systems to seal around penetrations, sheathing joints and window/door flanges. The antimicrobial coated fabric top layer provides an excellent bonding surface for cementitious and synthetic stucco coatings.



### PROTECTO SUPER STICK BUILDING TAPE®



A high performance window and door flashing tape designed to be applied down to -20°F (-28.88°C) without the use of primer or mechanical fasteners on most substrates. Provides a full 12 month UV exposure and contains no rubberized asphalt.



Protecto Wrap Company  
1955 S. Cherokee Street  
Denver, CO 80223  
(800) 759-9727  
[www.ProtectoWrap.com](http://www.ProtectoWrap.com)



CWRG-200 (7-25)